



3M™ Controltac™ Film Series 250Cv2 with Comply™ Adhesive version 2

DESCRIPTION	1
INTENDED APPLICATIONS	1
PERFORMANCE LIFE (UNPRINTED)	1
SHELF LIFE AND STORAGE	2
MAINTENANCE	2
PRINTING WITH THE GERBER EDGE®	2
PROTECTING GRAPHICS	2
CUTTING	2
SUBSTRATE PREPARATION	2
APPLICATION TECHNIQUES	3
PHYSICAL PROPERTIES	3
RELATED LITERATURE	4

DESCRIPTION

3M™ Controltac Film Series 250Cv2 with Comply™ Performance (version 2) is the latest film technology developed exclusively for Gerber. The new design of this Comply adhesive feature allows air to easily escape through micro-replicated channels under the film's surface without leaving any noticeable channel marks on the film surface itself. The result is a smooth, glossy graphic film that is faster and easier to apply than conventional films.

This 2-mil, repositionable film is EDGE READY™ and custom formulated exclusively for Gerber.

INTENDED APPLICATIONS

Series 250Cv2 film is ideal for both small and large graphics over corrugated and riveted surfaces such as tractor trailers, buses, and other fleet graphic applications. Series 250Cv2 can be used on a wide variety of substrates including ABS resins, aluminum, chrome, glass, fiberglass reinforced plastics, painted surfaces and flat or simple curved surfaces, with and without rivets. Series 250Cv2 Films have a grey-pigmented, pressure-sensitive adhesive, which allows for optimum color opacity.

This film is not recommended for use on stainless steel, non-3M films, or substrates that do not have a clean, smooth surface or have poor paint-to-substrate adhesion. It is also not intended for applications where petrochemical contact may occur. If petrochemical exposure is anticipated, refer to the section below on protecting graphics.

PERFORMANCE LIFE (UNPRINTED)

When applied vertically, Series 250Cv2 will have an expected performance life of 7 years. If applied non-vertically, the unprinted vinyl will have a performance life of 4 years.

Performance statements are based upon field experience and exposure tests conducted throughout the United States. Substrate selection, exposure angle, environmental conditions,

and maintenance of markings will affect actual performance. Continuous exposure in regions that experience maximum sunny days will result in decreased performance.

SHELF LIFE AND STORAGE

Apply film within one year of receipt. Printed graphics should also be applied within one year. Film and printed graphics (with or without premask) should be kept in a clean area free from excessive moisture and direct sunlight. Maintain temperature at less than 100°F (38°C).

Use a paper interleaf between layers of stacked or rolled printed materials. Do not stack printed graphics face to face.

MAINTENANCE

To clean printed graphics, use a mild, non-abrasive soap with a soft cloth or sponge. Avoid using alcohol-based cleansers or soaps containing grit or abrasives. Automated vehicle washing systems that use rotary cleaning brushes should also be avoided.

PRINTING WITH THE GERBER EDGE®

If your Gerber software does not have palettes for Controltac Film Series 250Cv2, use Gerber Controltac film 250C normal print settings.

GerberColor Spot (GCS) Series, Process Pro™ CMYK (GCP), Medal (GCM) Series and Transparent (GCT) Series foils can be used to print onto Series 250Cv2. (For information on the performance lives of GerberColor Foils, refer to the appropriate GerberColor Product Bulletin.)

PROTECTING GRAPHICS

Gerber Scientific Products, Inc. offers three products that are designed to protect vinyl and printed graphics.

Gerber Guard™ is a durable, dimensionally stable, glossy vinyl overlamine. This film has a petrochemical-resistant construction and is intended to be used when markings may be exposed to petrochemical spillage and/or severe handling conditions.

Gerber UVGuard will allow for simple cleaning of graffiti and mildew. The adhesive system of Gerber UVGuard is petrochemical resistant. (*The performance life of GerberColor Spot Pink will not be affected by Gerber UVGuard.)

GerberColor Abrasion Guard™ SPF is a clear, top-coat GerberColor Finishing Series (GCF) foil designed to protect graphics from moderate contact and exposure to harmful effects of UV rays.

CUTTING

Series 250Cv2 film can be cut on any 15" Gerber plotter. A 30° SuperSharp blade is recommended. Though plotters can be set to full speed for simple geometric shapes and panels over 6" high, slowing the speed of the plotter is found to optimize cut performance. User is advised to test cut before running entire job. This product is not recommended for complex contour cutting.

SUBSTRATE PREPARATION

Before applying your graphic, wash the surface of your substrate with warm water and detergent. Do not use soaps or other cleaners with lotions or creams as they will leave a residue. Thoroughly rinse the surface and allow it to completely dry.

Saturate a clean paper towel with a solvent-based cleaner and wipe the substrate surface. Be certain to follow all manufacturer safety guidelines when using any solvent. Dry the surface with a lint-free paper towel before the solvent evaporates.

If applying to glass, wipe the surface with a 2 to 1 mixture of water and isopropyl alcohol. Glass temperatures can vary across the surface. These temperature variations can produce stresses which may cause the glass to break. Use caution when applying to glass.

Some polycarbonate substrates may weaken when certain vinyl films are applied to them. Because of this possibility, the user will need to determine if safety items such as helmets, safety shields, and some windshields are compatible with their vinyl's adhesive.

Many paint systems (e.g. two-part urethane) and some polycarbonate substrates will outgas if they are not fully cured. Outgassing can cause permanent bubbling in most films; substrates should be tested for outgassing prior to final application.

Series 250Cv2 can be removed with heat or chemicals within 7 years. Be certain to follow all manufacturer safety guidelines when using heating devices or chemical solvents.

APPLICATION TECHNIQUES

Dry application should be used with Series 250Cv2. Panels can be overlapped. Graphics should be allowed to cure for 15 minutes prior to application.

IMPORTANT – PLEASE READ

Gerber standard tack application tape is required for all graphics produced with Gerber Digital Color Printing Systems. Due to the unique adhesive construction of Series 250Cv2, application tape can sometimes curl if exposed to the liner for prolonged periods of time. Therefore, to minimize contact between application tape and the liner, we suggest any of the following options for graphic application:

OPTION #1: Apply application tape immediately prior to installing graphic

OPTION #2: Trim excess application tape from graphic to reduce exposure to liner.

OPTION #3: If transporting graphic, secure the applied application tape to the back of the material liner with masking tape.

PHYSICAL PROPERTIES

Thickness (film)	2 mil
Adhesive	Pressure sensitive, repositionable
Adhesive Color	Grey
Liner	94#polyethylene-coated paper
Tensile Strength	5lb/in min at 73°F (0.9 kg/cm min at 23°C)
Dimensional Stability	.0015" (0.4 mm)
Application Temperatures:	
Flat Surfaces (with and without rivets)	40°F - 100°F (4°C - 38°C)
Corrugated Surfaces	50°F - 100°F (10°C - 38°C)
Removal Temperature	50°F (10°C) minimum (air and substrate)
Operating Temperature	-65°F to 225° F (-40°C to 107°C)

RELATED LITERATURE

GerberColor Spot (GCS) Series, GerberColor Process Pro (GCP) CMYK Series, GerberColor Medal (GCM) Series, GerberColor Transparent (GCT) Series GerberColor Finishing (GCF), and Gerber Guard Product Bulletins.

For help with questions concerning Gerber products, please call your distributor or Gerber Sales Support at 1-800-222-7446 or (860)644-1551.

Gerber EDGE and EDGE are Registered Trademark of Gerber Scientific Products, Inc.
GerberColor, GerberColor Process Pro CMYK, Gerber UVGuard, Gerber Guard, and Abrasion Guard SPF are Trademarks of Gerber Scientific Products, Inc.
3M, Controltac, and Comply are trademarks of the 3M Company.

©2011 Gerber Scientific, Inc. All Right Reserved

Category: EDGE READY™	FastFact #: 5572	Supplied by: Aftermarkets	Last Modified: 3/4/2011
------------------------------	-------------------------	----------------------------------	--------------------------------